

Wire Rope Slings

4-LEG BRIDLE SLINGS WITH EYE HOIST HOOKS

Wire Rope Diameter	EIPS Capacities in Tons 6x19 & 6x36			Master Links	Hooks Alloy (t)	Minimum Length Standard Eyes	Minimum Length Thimble Eyes
	60°	45°	30°				
1/4"	2.2	1.8	1.3	1/2"	1	1' 2"	10"
5/16"	3.5	2.8	2	5/8"	1	1' 6"	1'
3/8"	5	4.1	2.9	3/4"	1.5	1' 8"	1' 2"
7/16"	6.7	5.5	3.9	1"	2	2'	1' 4"
1/2"	8.8	7.1	5.1	1"	3	2' 3"	1' 6"
9/16"	11	9	6.4	1"	5	2' 8"	1' 8"
5/8"	14	11	7.8	1 1/4"	5	2' 10"	1' 10"
3/4"	19	16	11	1 1/2"	7	3' 5"	2' 2"
7/8"	26	21	15	1 1/2"	11	3' 11"	2' 5"
1"	34	28	20	1 3/4"	11	4' 6"	2' 9"
1 1/8"	42	34	24	2"	15	5' 2"	3' 2"
1 1/4"	51	42	30	2 1/4"	15	5' 8"	3' 8"
1 3/8"	62	50	36	2 1/4"	22	6'	3' 11"
1 1/2"	73	60	42	2 3/4"	22	7'	4' 2"
1 3/4"	98	80	57	3"	30	8'	5' 2"
2"	127	104	73	3 3/4"	37	9'	6' 1"
2 1/4"	154	126	89	4"	45	10'	6' 10"
2 1/2"	188	154	109	434,000#	60	11'	7' 5"
2 3/4"	225	184	130	520,000#		12'	8' 10"
3"	265	216	153	612,000#		13'	9' 6"
3 1/2"	352	287	203	812,000#		16'	11' 2"