

Crosby G-209 & G-2130 Anchor Shackle Chart

Working load limit (WLL), Crosby stock numbers, dimensions and weights for Crosby G-209 Screw Pin & G-2130 Bolt Type galvanized anchor shackles, 3/16" to 2-1/2" (0.33 to 55 Tons).

Crosby G-209 (Screw Pin) & G-2130 (Bolt Type) anchor shackles: WLL, stock numbers, dimensions and weights

G-209 and G-2130 shackles of the same nominal size share the same Working Load Limit and inside bow dimensions.

Nominal Size (D)	WLL (US tons)	Crosby Stock No.		Dimensions (inches)					Weight (lbs)	
		G-209 Screw	G-2130 Bolt	Pin Dia. (B)	Inside Width (E)	Inside Len. (C)	Mouth Width (A)	Outer Bow (G)	G-209	G-2130
3/16"	0.33 tons (660 lbs)	1018357	1019464	1/4" (0.25")	0.60"	0.88"	0.38"	0.98"	0.06	0.06
1/4"	0.5 tons (1,000 lbs)	1018375	1019466	5/16" (0.31")	0.78"	1.13"	0.47"	1.28"	0.10	0.11
5/16"	0.75 tons (1,500 lbs)	1018393	1019468	3/8" (0.38")	0.84"	1.22"	0.53"	1.47"	0.18	0.22
3/8"	1 ton (2,000 lbs)	1018419	1019470	7/16" (0.44")	1.03"	1.44"	0.66"	1.78"	0.31	0.33
7/16"	1.5 tons (3,000 lbs)	1018437	1019471	1/2" (0.50")	1.16"	1.69"	0.75"	2.03"	0.38	0.49
1/2"	2 tons (4,000 lbs)	1018455	1019472	5/8" (0.63")	1.31"	1.88"	0.81"	2.31"	0.72	0.79
5/8"	3.25 tons (6,500 lbs)	1018473	1019490	3/4" (0.75")	1.69"	2.38"	1.06"	2.94"	1.37	1.68
3/4"	4.75 tons (9,500 lbs)	1018491	1019515	7/8" (0.88")	2.00"	2.81"	1.25"	3.50"	2.35	2.72
7/8"	6.5 tons (13,000 lbs)	1018516	1019533	1" (1.00")	2.28"	3.31"	1.44"	4.03"	3.62	3.95
1"	8.5 tons (17,000 lbs)	1018534	1019551	1-1/8" (1.13")	2.69"	3.75"	1.69"	4.69"	5.03	5.66
1-1/8"	9.5 tons (19,000 lbs)	1018552	1019579	1-1/4" (1.25")	2.91"	4.25"	1.81"	5.16"	7.41	8.27
1-1/4"	12 tons (24,000 lbs)	1018570	1019597	1-3/8" (1.38")	3.25"	4.69"	2.03"	5.75"	9.50	11.71
1-3/8"	13.5 tons (27,000 lbs)	1018598	1019613	1-1/2" (1.50")	3.63"	5.25"	2.25"	6.38"	13.53	15.83
1-1/2"	17 tons (34,000 lbs)	1018614	1019631	1-5/8" (1.63")	3.88"	5.75"	2.38"	6.88"	17.20	19.00
1-3/4"	25 tons (50,000 lbs)	1018632	1019659	2" (2.00")	5.00"	7.00"	2.88"	8.86"	27.78	33.91
2"	35 tons (70,000 lbs)	1018650	1019677	2-1/4" (2.25")	5.75"	7.75"	3.25"	9.97"	45.00	52.25
2-1/2"	55 tons (110,000 lbs)	1018678	1019695	2-3/4" (2.75")	7.25"	10.50"	4.13"	12.87"	85.75	98.25

Specifications: Crosby G-209 (Screw Pin) & G-2130 (Bolt Type) forged carbon anchor shackles with alloy Red Pin®, 6:1 design factor, QUIC-CHECK® markings, hot-dip galvanized. Rated in US short tons (1 ton = 2,000 lbs); dimensions in inches; weights in lbs. Meets ASME B30.26, RR-C-271H & EN 13889.

Safety first: Never exceed the working load limit (WLL). Capacities shown are the manufacturer ratings listed on our product pages; the WLL marked on the shackle body governs. Capacities vary by brand, so do not swap brands assuming the same rating. Inspect shackles and pins before each use and remove damaged or worn shackles from service.

View this chart online: <https://slingsunlimited.com/learning-center/shackle-capacity-chart/>