

Polyester Round Sling Capacity Chart

Working load limits for every endless polyester round sling we sell, from the purple SP-300 to the black SP-9000, in pounds. Made in the USA; meets or exceeds ASME B30.9.

Endless polyester round sling: WLL in pounds by hitch			
Color & Code	Vertical (lbs)	Choker (lbs)	Basket (lbs)
● Purple SP-300	3,000	2,400	6,000
● Green SP-600	6,000	4,800	12,000
● Yellow SP-900	9,000	7,200	18,000
● Orange SP-1200	12,000	9,600	24,000
● Red SP-1400	14,000	11,200	28,000
● Orange SP-1700	17,000	13,600	34,000
● Blue SP-2200	22,000	17,600	44,000
● Orange SP-2600	26,000	20,800	52,000
● Orange SP-3200	32,000	25,600	64,000
● Orange SP-4000	40,000	32,000	80,000
● Orange SP-5300	53,000	42,400	106,000
● Black SP-6600	66,000	52,800	132,000
● Black SP-9000	90,000	72,000	180,000

Basket ratings are for a vertical basket hitch. Capacity drops as the sling angle flattens; do not rig below 30°. Round sling jacket colors help identify capacity at a glance; always confirm the rating on the sling tag.

Safety first: Never exceed the working load limit (WLL). Ratings shown are the manufacturer ratings listed on our product pages; always follow the WLL marked on the shackle or sling tag, which governs. Inspect all rigging before each use and remove damaged gear from service. Sling angle and hitch reduce capacity, so do not rig below 30°.

View this chart online: <https://slingsunlimited.com/learning-center/round-sling-capacity-chart/>